



The Sustainable Way Paving and Compaction Systems from Dynapac



Roland Egervári, Dynapac GmbH, Wardenburg



Fourteenth International Flexible Pavements Conference
Australian Technology Park, Sydney, Australia, 26 September 2011

DYNAPAC
Part of the Atlas Copco Group

Agenda



- § Dynapac's Sustainable Way
- § Asphalt paving – CO₂ emissions during the process chain
- § Paving the Sustainable Way: Compactasphalt® & Advanced Systems
- § Rolling the Sustainable Way: Low emissions and compaction control
- § Conclusion

Sustainability – A holistic approach

- § Create long term Value
 - For all stakeholders
- § Focus on Quality
 - Do things right from the beginning
 - Do the right things
- § Take Responsibility
 - Social
 - Environmental
 - Ethical
 - Economic



Main areas to address



Agenda



- § Dynapac's Sustainable Way
- § Asphalt paving – CO₂ emissions during the process chain
- § Paving the Sustainable Way: Advanced systems & Compactasphalt®
- § Rolling the Sustainable Way: Low emissions and compaction control
- § Conclusion

Asphalt paving and CO₂ emissions – The process chain

1) Mixed good production

- a) Indirect emissions: production of bitumen, aggregates and electricity
- b) Direct emissions discharged by the asphalt mixing plant



2) Machine usage

- a) Planer(s)
- b) Paver(s)
- c) Roller(s)
- d) Material transport (trucks)



3) Road closures

- a) Road closures result in traffic jams
 - à higher CO₂ emissions by cars
- a) Channelization of traffic causes more damage to the traffic lane where the traffic is running
- a) Standing traffic also creates a high vertical load



Asphalt paving: Energy consumption in the process chain

§ Energy consumption in the process chain

- Approx. 90 to 95% of the primary energy consumption as well as CO₂ emissions are generated during the quarrying and mixing process
- The remaining 5% to 10% is shared between transportation, paving and compaction


§ Resulting requirements for the paving process

- Higher quality through optimized paving processes
- Further reduction of the energy consumption and emissions for each stage of the process
- Reduced paving times for reduced burden on the user and residents


§ Which requirements are to be expected in the future?

- Higher quality standards for the paving result
- Possible limiting values for energy consumption and emissions per ton pavement

Asphalt paving: CO₂ emissions throughout the process chain



How to affect the major part of the cake as a machine producer?



How can DYNAPAC reduce CO₂ emissions in the upstream process chain?


By increasing the quality (durability) of the asphalt pavement!

Agenda



- § Dynapac's Sustainable Way
- § Asphalt paving – CO₂ emissions during the process chain
- § Paving the Sustainable Way: Compactasphalt® & advanced systems
- § Rolling the Sustainable Way: Low emissions and compaction control
- § Conclusion

Revolutionary new concepts



Henry Ford (1863-1947)



"If I had asked people what they wanted, they would have said faster horses."



Dynapac's breakthrough innovation: Compactasphalt® Revolutionary Sustainable!


§ Two layers in one process

- Better interlocking of the courses
- Paving time up to 50% less
- One paving crew for two layers

§ Significantly increased quality


§ Lower life cycle cost

- Material savings during paving (Direct saving)
- Significantly increased durability (Indirect saving)



DYNAPAC
Part of the Atlas Copco Group

Compactasphalt® – Material savings during the paving process



- § Halving the costly wearing course material
- § No bitumen emulsion is needed between the courses

Compactasphalt® – Example for material saving

Area	mass	unit	material specification / layer	density to/m ³	thickness cm	total	costs	costs calculation €/to	calculation costs €	real costs €
						material	material			
						to	€/to			
BAB A 14	290.000	m ²	Binder 0/22 S	2,331	8	54.079	58	58	3.136.594	3.136.594
						-----	-----	-----	-----	-----
									3.136.594	3.136.594
BAB A 14	290.000	m ²	SMA 0/8 S	2,304	4	26.726	88	88	2.351.923	2.351.923
						-----	-----	-----	-----	-----
									80.806	2.351.923
BAB A 14	290.000	m²	emulsion spray				0	0	43.500	43.500
total material costs standard paving									5.532.017	5.532.017
BAB A 14	290.000	m ²	Binder 0/22 S	2,331	10	67.599	58	58	3.920.742	3.920.742
						-----	-----	-----	-----	-----
									80.962	5.096.704
	290.000	m ²	SMA 0/8 S	2,304	2	13.363	88	88	1.175.962	1.175.962
total material costs compactasphalt									5.096.704	5.096.704
material profit compactasphalt									435.313	435.313

Reference: Johann Bunte GmbH, Papenburg, Germany, 2007; Highway Project calculation A14

Material savings: Your decision!



§ 43,500 € for tack coat, 290,000 m²



§ 43,500 € for a Hybrid sports car



§ 435,000 € for more costly mixed good



§ 435,000 €.....

DYNAPAC
Part of the Atlas Copco Group

Compactasphalt® – Revolutionary Sustainable!

§ Bitumen savings by:

- **Elimination of tack coat** as no tack coat between binder & top layer is needed
Conv. pavement needs $0.3 \text{ kg/m}^2 \times 290,000 \text{ m}^2 = \mathbf{87 \text{ tons bitumen was saved!}}$
- Halving the top layer, which has a higher bitumen content compared with the subjacent layers

§ Economic effects not considered in the calculation:

- Up to 50% reduced paving time = Less working hours

§ PPP project savings due to drastically reduced life cycle cost


Assumption: No repaving once during the conventional life cycle



$$290,000 \text{ m}^2 \times 11 \text{ €} = \mathbf{3,190,000 \text{ €}}$$

Compactasphalt® – Proven over time!

One of the most interesting test sections on the track has been the twin-layer OGFC placed in 2006. This section has a 9.5 mm nominal maximum aggregate size (NMAS) OGFC surface layer on top of a 12.5 mm NMAS OGFC layer. Both OGFC layers were placed with a special (and very large) paver built specifically to simultaneously place two HMA layers (see Fig. 4). After four years the twin-layer OGFC surface continues to be the smoothest, quietest and most effective section at eliminating water spray on the track.



- § Study by the University of Darmstadt on a 12 years old Compactasphalt Highway, A7
- § NCAT study also proved the high quality of Compactasphalt (Test 2006-2010)

The studies prove high quality of the Compactasphalt pavement

Compactasphalt jobsites world wide



Germany: ~ 3.500.000 m²

Netherlands: ~ 495.550 m²

Poland: ~ 410.000 m²

Russia: ~ 330.905 m²

Sweden: ~ 54.000 m²

Hungary: ~ 17.000 m²

China: ~ 2.205.000 m²




Compactasphalt jobsite impressions



DYNAPAC
Part of the Atlas Copco Group


Lowering CO₂ emissions during the paving process



- § Affecting the **small part of the cake** by reduced fuel consumption
- § Affecting the **largest part** by increased paving quality

Focus on quality: Safe Impact System

Patented, hydraulically extendable push rollers




NEW **SAFE IMPACT SYSTEM** ensures even surfaces even in case of heavy shock from the lorry!

This hydraulic anti shock system:

- 1) Reduces the impacts from material trucks
- 2) No screed marks in the mat
- 3) Extended dumping length (adjustments in docking, no damage to paver by long trucks)

§UNIQUE FEATURE IN THE MARKET!

Performance: Efficient cooling system



Modified fan installation

- § Separated from diesel engine → Less noise, less vibrations

Thermostatically controlled fan

- § Electronic motor management activates fan only when required
- § Fan-free rest period

§ Less fuel consumption


§ Noise reduction

§ Lower-noise cold starting

§ More rated output



Sustainable Heating Systems: Gas heated screeds



Energy consumption of both heating systems subject to ambient temperatures

§ Gas heated screed

§ Electric heated screed

Agenda



- § Dynapac's Sustainable Way
- § Asphalt paving – CO₂ emissions during the process chain
- § Paving the Sustainable Way: Compactasphalt® & advanced systems
- § Rolling the Sustainable Way: Low emissions and compaction control
- § Conclusion

Low emissions

CC224HF-CC324HF Tandem Rollers


- § 24 % less fuel consumption compared to previous models
- § 24 % less CO₂ emissions
- § Designed to secure high quality surfaces



24%

Compaction Control – DCA

Dynapac Compaction Analyzer - (Asphalt / Soil)



Accurate number of passes keep fuel consumption as low as possible

Pave
Comp



Dynapac CompLogger for soil compaction

DYNAPAC
Part of the Atlas Copco Group

- § Quality assurance of compaction process
- § Secures optimum number of passes to keep the fuel consumption as low as possible
- § Result is longer lasting roads

Low emissions

Aiming for the 1st zero diesel/gasoline fume emission roller concept



- § Overnight charging time
- § Recharged from a three-phase 400 V

Sustainable development



”Sustainable development meets the needs of the present without compromising the ability of future generations to meet their own needs”



DYNAPAC
Part of the Atlas Copco Group



***Driven by innovation –
committed to customer performance***

DYNAPAC
Part of the Atlas Copco Group